

Motor Driven Card Reader

V2BF

Motorised Card Reader for Magnetic and IC Cards

- Read magnetic cards, and Read/Write both smart and memory cards
- Able to update software program from host side by firmware download function.
- RS232 interface with user friendly command protocol for easy integration
- Rear ejection function and mechanical shutter prevents foreign objects and dust
- EMV Level1 approved

Read & Write Information



ISO1	ISO2	ISO3	JISII	IC Card	Memory Card (SLE4418/28/32/42)	Shutter	Interface	Type Name
R	R	R	-	R/W	R/W	Mechanical	RS232C	V2BF-01JS
R	R	-	R	R/W	R/W	Mechanical	RS232C	V2BF-0FJS

R : Read only R/W : Read & Write

Typical Applications

- Ticket vending machine
- Information & Payment KIOSK
- ID Card Checker
- Various Kiosk

Specifications

Part Number		V2BF		
Recommended card type		Magnetic card ISO1/2/3, JISII, IC Card, Memory Card (SLE4418/28/32/42)		
Card feedingspeed		250 mm/s ²		
Service life of magnetic head		1,200,000 passes or 5 years,		
Operating power supply		+12V DC Maximum 2.0 A		
Mounting location		Indoors—away from direct sunlight or wet, humid environment		
Ambient temperature	Operation	- 5° to 50° C		
Ambient temperature	Storage	- 20° to 70° C		
Ambient humidity	Operation	5% to 85% RH		
Ambient numbers	Storage	5% to 90% RH		
Vibration		10 to 150 Hz, single vibration width of 0.15 mm		
Shock		150 m/sec ² , three times in six directions		
Dimensions WxDxH		89 x 143 x 48 mm		
Weight		Approx. 400g		

V2BF

Engineering Data

