

FT190II

INDUSTRIAL THERMAL PANEL PRINTER

MAIN FEATURES

- 200dpi best thermal printing quality
- Paper width 58mm
- 50mm paper roll Ø
- Speed > of 30 mm/sec
- RS232 interface
- Barcodes: UPC-A, UPCE, EAN 13, EAN 8, CODE 39, INTERLEAVED 2- 5, CODABAR
- Fonts: European, International, Portuguese, Nordic
- MTBF > of 260.000 hours
- Sensors: paper end
- Dimensions (LxWxH): 119x119x45,5mm
- Weight: 362gr (without paper roll)

AVAILABLE VERSIONS

- FT190 II RS232 RTCK
- FT190 II RS232 RTCK + extended voltage input 9/40 V



EXCLUSIVE FEATURES

- Friendly installation and multipurpose fixing to different panel thicknesses
- When the front panel opens up, all the mechanical parts take a position which makes paper loading easier



FH190

INDUSTRIAL IMPACT PANEL PRINTER

MAIN FEATURES

- Impact dot matrix printing technology (8 pins)
- Paper width 58mm
- 50mm paper roll diameter
- Speed > of 30 mm/sec
- RS232 interface
- Barcodes: UPC-A, UPCE, EAN 13, EAN 8, CODE 39, INTERLEAVED 2- 5, CODABAR
- Fonts: European, International, Portuguese, Nordic
- MTBF > of 260.000 hours
- Sensors: paper end
- Dimensions (LxWxH): 119x119x45,5mm
- Weight: 362gr (without paper roll)

AVAILABLE VERSIONS

- FH190 RS232 RTCK 5V 24/40 columns
- FH190 RS232 RTCK 9/40V 24/40 columns



MOST COMMON APPLICATIONS

- measuring instruments
- weighing
- antitheft systems
- gas analysers
- panel tools