



SCANRANGER

Lecteur code-barres

Les lecteurs de codes-barres de la gamme Scanranger offrent des performances de lecture et décodage avancées pour un vaste choix d'applications : idéal dans le secteur des ventes pour les opérations de caisse et pour des applications de bureautique. Design ergonomique optimisé pour une prise stable et directe en cas d'utilisation pendant de longues périodes aussi. Structure robuste, résiste à des chutes de 1,5 m. Les sons et les LEDs aident à comprendre si le dispositif est en train de fonctionner.



ACCESSOIRES

What is in the box:

- Device, USB-RJ45 cable, user manual, warranty card

FICHE TECHNIQUE

	1D	2D	
	SR100NM	SR200NM	SR300NM
Type	Corded		Wireless
Interface	HID USB/ USB COM Port emulation	HID USB/USB COM	HID USB/USB COM
1D Barcodes supported	All UPC/EAN/JAN, EAN 128 code, Code 39, Code 39 full ASCII, Code 32/Italian Pharmacy, Code 128, CODABAR/NW 7, Interleave 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI/PLESSEY, Telepen, Code 93, Code 11, China Postage, GS1 DataBAR, GS1 Stacked codes	All UPC/EAN/JAN, EAN128 Code, Code 39, Code 39 Full ASCII, Code 128, CODABAR/NW7, Interleave 2 of 5, Industrial 2 of 5, Matrix 2 of 5, MSI/PLESSEY, Code 93, Code 11, China Postage, GS1 DataBar, GS1 Stacked codes	
2D Barcodes supported	-	PDF417, DataMatrix, QR Code	

COMMUNICATION

RF Standard	-	-	BT 4.0
Working distance	-	-	90 m (open environment)

OPTICAL

Optical sensor	2500 pixels	648 (H) x 488 (V) pixels	
Light source	RED LED (660 nm)	Aiming 610 nm red LED + white illumination LED	
Resolution	4 mil	5 mil	4 mil
Scan rate	100 scans/sec	60 fps	
Depth of field	10-390 mm	60 - 250 mm (13 mil)	74-203 mm (13 mil)
Indicator	Beeper and LED		
Print Contrast	-	Min. 30% @ UPC/EAN 100%	
Reading distance	-	up to 40 cm	

ELECTRICAL

Voltage	DC 5V		
----------------	-------	--	--

ENVIRONMENT

Operating temperature	0 °C to 40 °C		
Drop	1.5 m drops		
IP Code	IP3X		

PHYSICAL

Weight	190 g	-	-
Dimensions	82.53 mm (L) × 66.4 mm (W) × 162.08 mm (H)	-	-
Housing materials	ABS Plastic		

	1D	2D	
	SR100NM	SR200NM	SR300NM
BATTERY			
Battery type	-	-	Lithium-ion 3.7 V
Battery capacity	-	-	2.600 mAh good for 50.000 scans per charge
Charge	-	-	By USB power retrieving cable or cradle
<i>Product in the certification phase for the Brazilian Market</i>			

MODÈLES



994ED042600233
 BARCODE SCANNER
 SCANRANGER 1D CORDED
 SR100NM

995ED041800333
 BARCODE SCANNER
 SCANRANGER 2D CORDED
 SR200NM

995ED041600A33
 BARCODE SCANNER
 SCANRANGER 2D WIRELESS
 CRADLE SR300NM-CR

Les données techniques de ce site ne sont pas contraignantes et peuvent être modifiées sans préavis.
 Dernière mise à jour : 18 janvier 2022